



Cup filling-sealing



MACHINES

www.cemremakina.com

CEM-1

AYRAN DOLUM KAPATMA MAKİNASI

makinanın istasyonları

- 1- Kase düşürme istasyonu
- 2- Dolum istasyonu
- 3- Alüminyum kapak koyma istasyonu
- 4- yapıştırma
- 5- tarih atma
- 6- çıkış konveyörü



SOME SPECIFICATIONS

- | | |
|--------------------|--------------------------------------|
| - MODEL | : Cem-1 rotary new model |
| - CAPACITY | : 1500 psc / per hour min. capacity. |
| - CUPS SIZE | : Your cup size |
| - FILLING PRODUCTS | : Yogurt |
| - FILLING RANGE | : from 50 to 250 gramme. |
| - DIMENSIONS | : 1100 x 1100 x 2000 mm appr. |
| - WEIGHT | : 350 Kg appr. |
| - PACKING | : Wooden Chest |
| - ELECTRICAL | : Relay system 380 V. |

Döner tablolu ayran dolum kapatma makinası

The machine has third photocell check-points

-First photocell to control for filling if there is any cup or not Thanks to this photocell system, the machine would not waste the product. If there is no cups, then the machine would not fill.

- Second photocell to control for filling if there is any cup or not Thanks to this photocell system, the machine would not waste the product. If there is no cups, then the machine would not fill.

-Third photocell control for the aluminum lids if there is no cup or not, thanks to this system if there is no cup then the machine would not waste the aluminum lids

GENERAL OPERATING OF THE MACHINE STATIONS

ROTARY TABLE

: Rotary Table turns by mechanical indexer.

CUP DROP STATION

: plastic cups dropping by pneumatical

FILLING STATION

: Filling station work by volumetric(pump). filling funnel capacity 40 litre appr. accuracy in filling is about %2. Filling station could fill high visicocity yogurt.

PLACING LID STATION

: Lids on magazine are Putting on cups by vacuuming pneumatical

SEALING

: Lids are sealed to cups by heat pneumatical

DATING

: The machine dates by ink. Two-line dating is available

EXIT

: Cups are taken up to outlet conveyor. Lengh is

2015 model ayran dolum makinası

